

Malware galéria: a kód vizuális arca

Attila Mester

attila.mester@ubbcluj.ro

Malware gallery: visualizing the code

Babeş–Bolyai University, Romania
Faculty of Mathematics and Computer Science

29th November 2025



The need for automated malware analysis




Figure 1: New malicious samples: 300k/day, worldwide (AV-TEST¹, March 2025).

¹<https://www.av-test.org>

1. Introduction

Literature

2. Model representations

3. Static call graph feature

4. Attribution with CNN

5. Malflow

Malware analysis – the textbook approach




Figure 2: Malware analysis – taxonomy according to (Ucci, Aniello, and Baldoni 2019).

Survey of previous research on malware




Figure 3: ≈ 100 research papers categorized according to *extracted features* and *algorithms*. Most frequent: *API/sys calls*.

Feature 1: byte histogram




Figure 4: Byte distribution of infected Notepad.exe – 1. infection

Feature 1: byte histogram




Figure 5: Byte distribution of infected Notepad.exe – 2. infection

Feature 1: byte histogram




Figure 6: Byte distribution of infected Notepad.exe – 3. infection

Feature 2: instruction counts




Figure 9: Instructions of infected Notepad exe – 3. infection

Feature 3: call graph

- static = obtained by disassembly – e.g. **IDA²**, **Radare2³**
- node = function (DLL / subroutine)
- link = function call
- usage:
 - similarity measure? **NP-hard**
 - signature database? **metamorphic evasion**

²<https://hex-rays.com/ida-pro>

³<https://rada.re>




Figure 10: Sample call graph obtained by Radare2.




Figure 11: 8 MB malware file: 7k functions, 300k instructions





Figure 12: Static call graph of metamorphic virus generations – Gephi⁴, Force Atlas layout.

⁴<https://gephi.org>

Malware family classification using CNN on the encoded call graph



Converting a malware into an RGB image

- **image**: list of instruction-pixels (900 instructions = 30x30 image)
instruction: **[bnd?] [prefix?] mnemonic [param1 [param2, ...]]**
2019 mnemonics, 11 prefixes
- **(FE)** Full Encoding: *mnemonic, prefix, bnd, two parameters*
- **(PE1)** Partial Encoding: mnemonic, prefix, bnd
- **(PE2)** Partial Encoding: only mnemonic

Simple hex dump






Encoding **FE**Encoding **PE1**Encoding **PE2****ainslot** sample**allapple** sample

Figure 13: Comparing different instruction encodings and the simple hex dump image on different malware families.




Figure 14: Call graphs and RGB images of metamorphic virus generations.

- **Code:** <https://github.com/attilamester/malflow>
- **Dataset:** <https://www.kaggle.com/datasets/amester/malflow>
- **Python package:** <https://test.pypi.org/project/malflow/>
- **Docker:** <https://hub.docker.com/repository/docker/attilamester/radare2>

```
$ malflow --help
usage: malflow [-h] [--version] {info,nodes,edges,export,image,dfs} ...

Malflow - Static analysis tool for PE executables using Radare2

positional arguments:
  {info,nodes,edges,export,image,dfs}

      info                Available commands
      nodes               Analyze PE file and display call graph metadata
      edges               List and query nodes
      export               Display call graph edges
      image                Export call graph to various formats
      dfs                 Generate image representation of call graph
                        Perform DFS traversal

optional arguments:
  -h, --help              show this help message and exit
  --version                show program's version number and exit
```

Thank you for your attention! Questions?



attilamester.github.io/call-graph